B1001 200ml - Technical Data Sheet



Description

B1001 200ml is an aerosol-applied cyanoacrylate accelerant which, once applied to a difficult to bond substrate, significantly increases the cure speed of cyanoacrylate adhesive. The product is used primarily on wood mitre joints or on porous, acidic or difficult to bond surfaces.

Achieve an instant bond with no mess. Allow 10 seconds for positioning.

B1001 200ml bonds to MDF, wood, chipboard, rubber, metals, most plastics, Perspex, ceramics, aluminium and much more. It is perfect for all cornice and profile mitres, trims, picture frames, MDF skirting and architrave joints, worktop end strips, PVCu trims and much more.

Physical Properties

Consistency	Liquid
Colour	Colourless
Specific Gravity	0.79 g/cm ³ approx
VOC level	605 g/l
Solvent	 Low boiling point modified naphtha-naphtha (petroleum), solvent-refined light Propane Butane Isobutane
Size of can	200ml

Directions for Use

- 1. Ensure both surfaces to be bonded are clean, dry and free from grease.
- 2. Lightly spray one of the surfaces to be bonded with the activator.
- 3. Allow the activator to dry.
- 4. Apply a thin layer of the cyanoacrylate to the other surface.
- 5. Bring both surfaces together to achieve a bond. Depending on the substrates being used and temperature a rapid bond will be typically formed in 2-10 seconds.

Precaution

- 1. Extremely flammable.
- 2. Keep in well ventilated place away from sources of ignition.
- 3. Do not breathe vapour or empty in drains.
- 4. Do not pierce or burn after use.
- 5. The activator should be stored between 5 and 30 degrees centigrade, away from direct sunlight.

Please consult the B1001 200ml Health & Safety Data Sheet for statutory regulation information.

Information relating to the products of Bondrite Adhesive Limited is based on tests carried out under laboratory conditions. If any of our products are not used in accordance with our instructions or are used under conditions which vary from our laboratory, they may not perform in accordance with any information provided and Bondrite shall not have any liability in this case. Bondrite will accordingly provide samples of our products, on request and free of charge, for customers to carry out their own tests as to suitability of our product for their purposes and as used in their intended environment.

Purchase from Bondrite