

## W5000XL – Technical Data Sheet



Bondrite Adhesives Limited  
Unit 3H  
Sileby Road Industrial Estate  
Barrow-Upon-Soar  
Leicestershire LE12 8LP  
Tel: 01509 815550

### Description

**W5000XL** is a high quality wood adhesive for use in joinery applications where D4 water resistance is required. Examples of use include:

- exterior furniture,
- windows,
- doors,
- high pressure laminates,
- kitchen and bathroom furniture.

**W5000XL** is suitable for use with a roller or wheel type machine.

**W5000XL** will bond most hard and soft woods, chipboard, MDF, plywood and HPL. It offers the user a high water resistance to D4 EN204.

### Physical Properties

|                          |                |
|--------------------------|----------------|
| <b>Polymer Base</b>      | PVA            |
| <b>Solids</b>            | 49-53%         |
| <b>Viscosity</b>         | 3,500-9,500cPs |
| <b>Storage</b>           | 5-25°C         |
| <b>Dilution</b>          | Use neat       |
| <b>Usage temperature</b> | Ambient        |

### Precaution

Store between 5 - 25°C. Storage outside of the suggested temperature range could adversely affect the properties of the adhesive

**Please consult the W5000XL Health & Safety Data Sheet for statutory regulation information.**

Information relating to the products of Bondrite Adhesive Limited is based on tests carried out under laboratory conditions. If any of our products are not used in accordance with our instructions or are used under conditions which vary from our laboratory, they may not perform in accordance with any information provided and Bondrite shall not have any liability in this case. Bondrite will accordingly provide samples of our products, on request and free of charge, for Customers to carry out their own tests as to suitability of our product for their purposes and as used in their intended environment.

Purchase from Bondrite