

W3003 – Technical Data Sheet



Bondrite Adhesives Limited
Unit 3H
Sileby Road Industrial Estate
Barrow-Upon-Soar
Leicestershire LE12 8LP
Tel: 01509 815550

Description

W3003 is a high quality, general purpose, high solids PVA adhesive for use in padding and lamination of paper to board and board to board applications. It is particularly useful for applications where a long open-time is required. It is suitable for use with all jet application machines.

W3003 offers the user the following benefits:

- Clean running
- Minimum down time
- Easy cleaning from glue tanks and machine parts
- Good adhesion to a wide range of materials
- Excellent initial tack with long open time. Ideal for handwork and high speed machines
- Exceptional quality control produces unrivalled consistency

Physical Properties

Polymer Base	PVA
Solids	51 - 55%
Viscosity	2000 - 3000 mPas
Storage	5-20°C
Dilution	Use neat
Usage temperature	Ambient

Precaution

All ingredients meet the requirements of FDA CFR21 175.105 Adhesives, therefore it is safe for the packaging required in transporting or holding of food.

Please consult the W3003 Health & Safety Data Sheet for statutory regulation information.

Information relating to the products of Bondrite Adhesive Limited is based on tests carried out under laboratory conditions. If any of our products are not used in accordance with our instructions or are used under conditions which vary from our laboratory, they may not perform in accordance with any information provided and Bondrite shall not have any liability in this case. Bondrite will accordingly provide samples of our products, on request and free of charge, for Customers to carry out their own tests as to suitability of our product for their purposes and as used in their intended environment.

Purchase from Bondrite