

W3001 – Technical Data Sheet



Bondrite Adhesives Limited
Unit 3H
Sileby Road Industrial Estate
Barrow-Upon-Soar
Leicestershire LE12 8LP
Tel: 01509 815550

Description

W3001 is a high quality wood PVA adhesive for use in joinery applications where D3 water resistance is required. Examples of use include:

- Wooden furniture,
- Internal windows & doors,
- High pressure laminates,
- Kitchen and bathroom furniture
- Worktops

W3001 will bond most hard and soft woods, chipboard, MDF, plywood and HPL.

W3001 is suitable for use with all roller systems.

Physical Properties

Polymer Base	PVA
Solids	48-51%
Viscosity	7,000-12,000cPs
Storage	5-20°C
Dilution	Use neat
Usage temperature	Ambient

Precaution

It offers the user a high water resistance to D3 EN204.

Test Report

REGULATION OR PROTOCOL	CONCLUSION	VERSION OF REGULATION OR PROTOCOL
French VOC Regulation	A+	Regulation of March & April 2011 (DEVL1101903D & DEVL1104857A)
AgBB	Pass	AgBB of February 2015. DIBt of October 2010
Indoor Air Comfort®	Pass	Indoor Air Comfort 6.0 of February 2017
Indoor Air Comfort Gold®	Pass	Indoor Air Comfort GOLD 6.0 of February 2017
Blue Angel (RAL UZ 113)	Pass	RAL UZ 113 for "Low-Emission Floor Covering Adhesives and other Installation Materials" (Version June 2011)

Please consult the W3001 Health & Safety Data Sheet for statutory regulation information.

Information relating to the products of Bondrite Adhesive Limited is based on tests carried out under laboratory conditions. If any of our products are not used in accordance with our instructions or are used under conditions which vary from our laboratory, they may not perform in accordance with any information provided and Bondrite shall not have any liability in this case. Bondrite will accordingly provide samples of our products, on request and free of charge, for Customers to carry out their own tests as to suitability of our product for their purposes and as used in their intended environment.